



Prefabricated floors

Technical specifications

is a product of



Characteristics:

- Stackable up to 40m² floor per pallet
- Assembly up to 25m² floor per person/ per hour
- Cables and pipes can be concealed underneath the floor
- Sustainable system

Floorboard: Okumé plywood 1000 x 1000 x 45 mm

- Framework of ± 70 mm around 30 mm okumé
- Pinewood cross in the middle, filled with polystyrene
- Bottom plate 5 mm WBP okumé
- Weight: 12 kg
- Fire classification: 2
- Maximum capacity of 4 adapting feet: ± 800 kg per m²
- Maximum capacity of 9 adapting feet: ± 2000 kg per m²
- Horizontal stainless steel fixer pal adjustable with Allen key 6mm

Floorboard: Poplar plywood 1000 x 1000 x 45 mm

- Massive 45 mm thick poplar plywood
- Weight: 22 kg
- Maximum capacity of 4 adapting feet: ± 800 kg per m²
- Maximum capacity of 9 adapting feet: ± 2000 kg per m²
- Horizontal stainless steel fixer pal adjustable with Allen key 6mm
- Available in: Floorboard 1000 x 500 x 45/50mm
- Available in: Waterboard 1000 x 1000 x 45 mm
- Available in: Wheelchair ramp 1000 x 992 x 45 mm
- Diagonal plates available

Adjustable foot:

- High-tech plastic nylon
- Adjustable from 55 mm to 105 mm (100 to 150 mm above the floor)
- Galvanized 12 mm axle
- Adjustable with 6mm Allen key
- Maximum load: 3000 kg
- Weight: 187 gram
- Fire classification: 2

